



Client _____ Quantity _____
 Project _____ Position _____

Vision Industry W201K U

Model: W201KUR-2D

Cod: W80420214001

Technical data

Max capacity:	4 trolleys GN2/1, EN60x80
Temperature range:	-40°+10°C
Ventilation range:	25% - 100%
Humidifier:	Non disponibile
Refrigerant unit:	Remote
Yield +90 / +3:	800 Kg
Yield +90 / -18:	640 Kg
Cooling gas:	R404/R452
Defrost:	Forced air
Valve:	Electronic expansion valve
Dimensions:	1600×4680×2510 mm
Packing dimensions:	N°3× 2755×1730×2000 mm
Gross weight:	1.640 Kg
Voltage:	400-415 V - 50-60 Hz
Total rate:	6080 W
Absorbed Current:	16,86 A
Cooling capacity:	82440 W*

Features

Functions:	Blast chilling, shock freezing, continuous cycle
Control:	7" touch screen display with USB port
Doors:	Dictator closure to absorb sudden changes in pressure when opening and closing doors
Door gasket:	Magnetic, triple chamber and easily replaceable
Core probe:	Needle probe with 1 reading point, quick-release and easily replaceable
Insulation:	100 mm thickness - CFC/HCFC free
Exterior/interior finishing:	Internal and external in "linen canvas" steel
Inner corners:	Rounded base 20 mm
Handle:	In AISI 304 stainless steel
Cosmo:	Wi-Fi remote control system

Remote unit technical data

Voltage:	400-415 V 3N - 50 Hz
Cooling gas:	R404-R452a
HP unit:	23
Gross weight:	521 Kg
Dimensions:	2180×1170×1208 mm
Cooling capacity:	Evap. -10°C Cond. +45°C

Accessories and variants

Pavimento h 20 mm, rampa di accesso inclusa

Reverse door opening from standard

Door opening turning and control panel inversion

Door stop 100°

Sonda al cuore 3 punti di lettura

Sonda al cuore riscaldata 1 punto di lettura

Winter kit -20°C

Winter kit -40°C

Predisposition for connection to CO2 remote control unit

Other special voltage

Offene Verflüssigungssätze 4GE-23Y W101K-W150K

Unità condensante 4GE-23Y abb. W101K-W150K carenata sil.

Unità condensante 4GE-23Y abb. W101K-W150K carenata cond. remoto

PVC ventilation profiles W200K

Ramp 100 mm high. Length 913 mm W40

Ramp 140 mm high. Length 1390 mm W40

Trolley GN1/1 20 trays 598x530x1630 mm

Trolley EN60x40 20 trays 460x620x1750 mm

Trolley GN2/1 20 trays 660x720x1750 mm

Trolley EN60x80 20 trays 660x820x1750 mm

Purity C Quell ST 50 filter cartridge

Sanitizing detergent


Sterilizing UV lamp (U version)

COSMO - wi-fi control

Cosmo is the wi-fi technology that allow to connect, update and monitor with a smartphone the VISION blast chiller. VISION is also a Cosmo hub and allow remote supervision of the Coldline devices connected to it. From the app you can check the operating conditions of each machine and receive alerts in the event of abnormal operation.

*The installation requires a kit for the replacement of the racks

Technical draw



A: Power supply cable outlet

B: Condensation water drain

C: Floor grid for condensate drainage (recommended)

I: Internal led lighting

L: Door clear opening dimension

N: PVC ventilation profiles

R: Gas output pipes

W: Water mains connection for humidifier - 3/4" female. Unloading not required

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.